



WaStop® Inline Check Valve Technical Specification Stainless Steel AISI 316


Model no.:	WS183-S2-316	WS183-S3-316	WS183-S4-316
Nominal Size:	200 mm		
Pipe:	Stainless Steel AISI 316		
Membrane:	Silicone		
Fasteners:	Marine grade stainless steel (AISI 316)		

Technical data:	Soft (S2)	Standard (S3)	Hard (S4)
Max. back pressure*:	3 mmH ₂ O	5 mmH ₂ O	8 mmH ₂ O
Horizontal opening pressure*:	163 mmH ₂ O	266** mmH ₂ O	325** mmH ₂ O
Horizontal closing pressure*:	84 mmH ₂ O	118** mmH ₂ O	1555** mmH ₂ O
Submerged opening pressure*:	182** mmH ₂ O	209** mmH ₂ O	234** mmH ₂ O
Submerged closing pressure*:	52** mmH ₂ O	60** mmH ₂ O	67** mmH ₂ O
Vertical opening pressure*:	263 mmH ₂ O	317** mmH ₂ O	349** mmH ₂ O
Vertical closing pressure*:	165** mmH ₂ O	285** mmH ₂ O	314** mmH ₂ O

*) +/- 15% **) Modeled value
 - Values measured from bottom of pipe.
 - Tests performed at room temperature (16-20 °C).

Max Flow	m/s	l/s
	2	64

- Higher flows requires custom valve, contact Wapro
 - Flange installation is highly recommended at flows above 2 m/s



In the submerged case opening pressure [mmH₂O / inH₂O] is the difference between the water level upstream and the water level downstream and in the open-air case to the invert of the pipe. In vertical applications, the vertical opening pressure is measured from the outlet of the WaStop.

