



## WaStop® Inline Check Valve Technical Specification Stainless Steel AISI 304/316

<b>Model no.:</b>	WS283-S2-304/316	WS283-S3-304/316	WS283-S4-304/316
<b>Nominal Size:</b>	300 mm		
<b>Pipe:</b>	Stainless Steel AISI 304/316		
<b>Membrane:</b>	Silicone		
<b>Fasteners:</b>	Marine grade stainless steel (AISI 316)		

Technical data:	Soft (S2)	Standard (S3)	Hard (S4)
Max. back pressure*:	3 mH <sub>2</sub> O	5 mH <sub>2</sub> O	8 mH <sub>2</sub> O
Horizontal opening pressure*:	191 mmH <sub>2</sub> O	209** mmH <sub>2</sub> O	234** mmH <sub>2</sub> O
Horizontal closing pressure*:	108 mmH <sub>2</sub> O	106** mmH <sub>2</sub> O	119** mmH <sub>2</sub> O
Submerged opening pressure*:	136** mmH <sub>2</sub> O	157** mmH <sub>2</sub> O	176** mmH <sub>2</sub> O
Submerged closing pressure*:	48** mmH <sub>2</sub> O	56** mmH <sub>2</sub> O	62** mmH <sub>2</sub> O
Vertical opening pressure*:	298 mmH <sub>2</sub> O	375** mmH <sub>2</sub> O	413** mmH <sub>2</sub> O
Vertical closing pressure*:	195** mmH <sub>2</sub> O	188** mmH <sub>2</sub> O	207** mmH <sub>2</sub> O

\*) +/- 15% \*\*) Modeled value  
 - Values measured from bottom of pipe.  
 - Tests performed at room temperature (16-20 °C).

Max Flow	m/s	l/s
	3	214

- Higher flows requires custom valve, contact Wapro  
 - Flange installation is highly recommended at flows above 2 m/s



In the submerged case opening pressure [mmH<sub>2</sub>O / inH<sub>2</sub>O] is the difference between the water level upstream and the water level downstream and in the open-air case to the invert of the pipe. In vertical applications, the vertical opening pressure is measured from the outlet of the WaStop.

