



## WaStop® Inline Check Valve Technical Specification PVC

<b>Model no.:</b>	WS110PVC-S2	WS110PVC-S3	WS110PVC-S4
<b>Nominal Size:</b>	110 mm		
<b>Pipe:</b>	PVC		
<b>Membrane:</b>	Silicone		
<b>Fasteners:</b>	Marine grade stainless steel (AISI 316)		

Technical data:	Soft (S2)	Standard (S3)	Hard (S4)
Max. back pressure*:	3 mmH <sub>2</sub> O	5 mmH <sub>2</sub> O	8 mmH <sub>2</sub> O
Horizontal opening pressure*:	142 mmH <sub>2</sub> O	213** mmH <sub>2</sub> O	270** mmH <sub>2</sub> O
Horizontal closing pressure*:	63 mmH <sub>2</sub> O	69** mmH <sub>2</sub> O	72** mmH <sub>2</sub> O
Submerged opening pressure*:	157** mmH <sub>2</sub> O	180** mmH <sub>2</sub> O	202** mmH <sub>2</sub> O
Submerged closing pressure*:	28** mmH <sub>2</sub> O	32** mmH <sub>2</sub> O	36** mmH <sub>2</sub> O
Vertical opening pressure*:	228 mmH <sub>2</sub> O	253** mmH <sub>2</sub> O	278** mmH <sub>2</sub> O
Vertical closing pressure*:	119** mmH <sub>2</sub> O	132** mmH <sub>2</sub> O	145** mmH <sub>2</sub> O

\*) +/- 15% \*\*) Modeled value


- Values measured from bottom of pipe.

- Tests performed at room temperature (16-20 °C).

Max Flow	m/s	l/s
	2	20

- Higher flows requires custom valve, contact Wapro

- Flange installation is highly recommended at flows above 2 m/s



In the submerged case opening pressure [mmH<sub>2</sub>O / inH<sub>2</sub>O] is the difference between the water level upstream and the water level downstream and in the open-air case to the invert of the pipe. In vertical applications, the vertical opening pressure is measured from the outlet of the WaStop.

