

WaStop® Inline Check Valve Technical Specification Stainless Steel AISI 304/316


Model no.:	N/A	WS340-S3-304/316-SH	N/A
Nominal Size:	350 mm		
Pipe:	Stainless Steel AISI 304/316		
Membrane:	Polyurethane		
Fasteners:	Marine grade stainless steel (AISI 316)		

Technical data:	Soft (S2)	Standard (S3)	Hard (S4)
Max. back pressure*:	N/A mmH ₂ O	3 mmH ₂ O	3 mmH ₂ O
Horizontal opening pressure*:	N/A mmH ₂ O	325** mmH ₂ O	N/A** mmH ₂ O
Horizontal closing pressure*:	N/A mmH ₂ O	195** mmH ₂ O	N/A** mmH ₂ O
Submerged opening pressure*:	N/A** mmH ₂ O	205** mmH ₂ O	N/A** mmH ₂ O
Submerged closing pressure*:	N/A** mmH ₂ O	60** mmH ₂ O	N/A** mmH ₂ O
Vertical opening pressure*:	N/A mmH ₂ O	350** mmH ₂ O	N/A** mmH ₂ O
Vertical closing pressure*:	N/A** mmH ₂ O	205** mmH ₂ O	N/A** mmH ₂ O

*) +/- 15% **) Modeled value
 - Values measured from bottom of pipe.
 - Tests performed at room temperature (16-20°C).

Max Flow	m/s	l/s
	3	290

- Higher flows requires custom valve, contact Wapro
 - Flange installation is highly recommended at flows above 2 m/s



In the submerged case opening pressure [mmH₂O /inH₂O] is the difference between the water level upstream and the water level downstream and in the open-air case to the invert of the pipe. In vertical applications, the vertical opening pressure is measured from the outlet of the WaStop.